

## Residential METAL ROOFING






### **Panel Options**



**SL-18** 

The SL-16® roof panel system offers a sleek contemporary profile, installed with concealed fasteners, making it ideal for residential applications. SL-16® panels are available with striations or striations and minor ribs. The SL-16® panel cannot be end lapped and must be installed over a solid, waterproofed deck when used as a roof panel.



Applications: Roof Coverage Widths: 16" Rib Height: 1" Minimum Slope: 3:12

Panel Attachment: Concealed Fastening System


Gauges: 29 (standard); 26 (optional)

Finishes: Striations (standard); Minor Rib Striations (optional) Coatings: Galvalume Plus®, Signature® 200, Signature® 300,

Signature® 300 Metallic

**Imperial Rib** 

The Imperial Rib® panel system is an exposed fastened offering that can be used for both roof and wall applications. Imperial Rib® is ideal for residential, agricultural, light commercial and storage buildings. It also works well for canopies.



Applications: Roof and Wall Coverage Widths: 36" Rib Spacing: 9" on center Rib Height: 3/4"

Rib Height: ¾" Minimum Slope: 3:12

Panel Attachment: Exposed Fastening System

**Gauges**: 29 (standard); 26 (optional) **Finishes**: Smooth (standard);


Embossed (optional)

Coatings: Galvalume Plus®, Signature® 200



PBR

PBR panel is commonly used for a wide variety of applications, including residential and agricultural. PBR is a structural panel and an exposed fastener panel that can be used for both roof and wall applications. The minimum roof slope for PBR is ½:12.




Applications: Roof and Wall Coverage Width: 36" Rib Spacing: 12" on Center

Rib Height: 1¼" Minimum Slope: ½:12

Panel Attachment: Exposed Fastening System
Gauges: 26 (standard); 22, 24 and 29 (optional)
Finishes: Smooth (standard); Embossed (optional)
Coatings: Galvalume Plus', Signature' 200, Signature' 300

PBU

PBU can be installed directly over purlins or joists. PBU offers the versatility of being used in both vertical and horizontal applications to give designers a contemporary appearance for their building project. PBU is recommended for 1:12 or greater roof slopes.




Applications: Roof and Wall Coverage Width: 36" Rib Spacing: 6" on Center

Rib Height: ¾" Minimum Slope: 1:12

Panel Attachment: Exposed Fastening System Gauges: 26 (standard); 22, 24 and 29 (optional) Finishes: Smooth (standard); Embossed (optional) Coatings: Galvalume Plus', Signature' 200, Signature' 300

5V Crimp®

5V Crimp® is a popular aesthetically-pleasing solution for residential applications. The 5V Crimp® panel is one of the oldest, and most trusted, in the industry. The low-rib, exposed fastener panel requires a solid roof deck with a waterproof membrane.



Applications: Roof Coverage Width: 24" Rib Spacing: 12" on Center

Rib Height: ½" Minimum Slope: 3:12

Panel Attachment: Exposed Fastening System Gauges: 32, 29 (standard); 26 (optional)


Finishes: Smooth (standard)

Coatings: Galvalume Plus\*, Signature\* 200, G-40 Galvanized



# \_okSeam®

A snap-together standing seam, concealed fastener roof system, LokSeam® panels are available in 12-inch, 16-inch and 18-inch widths. Available in a wide variety of colors including metallic, this profile adds beauty and longevity to your home. LokSeam® panels can be installed over open framing or a solid substructure and are capable of transitioning from roof to fascia with the use of a rib cover. LokSeam® does not require a solid substructure for support.



Application: Roof

Coverage Widths: 12", 16" and 18"

Minimum Slope: 3:12

Panel Attachment: Concealed Fastening System, Standard


and UL 90 Clips

Gauges: 24 (standard); 22 (12", 16", 18") and 26 (12") (optional) Finishes: Striated (standard); Embossed Striated (optional) Coatings: Galvalume Plus', Signature' 200, Signature' 300,

Signature 300 Metallic

# **Rustic Trail**

The Rustic Trail panel is the ultimate roofing panel for innovative builders who choose the beautifully weathered look of rusted steel. Designed to naturally oxidize, the Rustic Trail Panels provide a picturesque western look for that home owner who wants to stand out.



Applications: Roof & Wall

Coverage Widths: 32" wall, 29.33" roof
Panel Attachment: Exposed Fastening System

Gauges: 22 (standard)
Minimum Slope: 3:12
Rib Spacing: 2.67" on center

Rib Height: 7/8"

### **Warranty Options**

# Premiun

#### Gauge

29

#### Substrate

Galvalume

#### **Paint System**

Signature Series Valspar Weather Siliconized Polyester 18 Colors

#### Warranty

40-Year Film Integrity 30-Year Chalk & Fade 25-Year Substrate

# Select40

#### Gauge

29

#### Substrate

Galvalume

#### **Paint System**

Signature Series Valspar Weather Siliconized Polyester 12 Colors

#### Warranty

40-Year Film Integrity 30-Year Chalk & Fade

### cono20

#### Gauge

29

#### Substrate

Various

#### **Paint System**

Signature Series Valspar Weather Siliconized Polyester 10 Colors

#### Warranty

20-Year Film Integrity 15-Year Chalk & Fade

		, 29°	, Vo.	2/3/29	7
	Buckskin 727				
	Burgundy 717				
	Burnished Slate 212				
	Charcoal Gray 219				
	Clay 238				
	Coal Black 203				
	Cobalt Blue 209				
	Desert Sand 217				
	Evergreen 234				
	Galvalume Plus® 018				
	Galvanized 001				
	Gray 725				
	Hawaiian Blue 204				
	Ivy Green 712				
	Koko Brown 215		0	0	
	Light Stone 206				
	Polar White 202			0	
	Radiant Red 730				
	Regal White 702		0	0	
	Rustic Red 207				
	Saddle Tan 221		0	0	0
	Vintage White 230				

### Paint Finishes

#### Signature 200 & 300

ABC's Signature paint systems utilize an SMP (silicon-modified polyester) finish available in a number of high-end colors.


#### Kynar 500

ABC also provides several custom, special order colors in KYNAR 500, PVDF resin-based coating or finish.

\*Signature is a registered trademark of the NCI group, Inc. KYNAR 500 is a registered trademark of Arkema, Inc.

#### Digital Imaging and Roof Estimating

At ABC we've designed residential solutions with you in mind. Whether you're interested in satellite mapping of your roof, a digital measurement of your roof area and lines, or a consultation on what panel type and color would be best suited for your home, ABC is here to help.













ABCMetalRoofing.com shop.ABCMetalRoofing.com Adel, GA 877.595.6604 Frankfort, KY 877.780.2119 Lubbock, TX 877.695.0477 Memphis, TN 877.774.0157 Mt. Pleasant, IA 877.768.9460 Oklahoma City, OK 877.795.4399 Phoenix, AZ 877.774.6219 Rome, NY 877.785.0821 Salt Lake City, UT 877.814.1419

Descriptions and specifications contained herein were in effect at the time this publication was approved for printing. In a continuing effort to refine and improve our products, American Building Components reserves the right to discontinue products at any time or change specifications and/or designs without incurring obligation. To ensure you have the latest information available, please inquire or visit our website at www.abcmetalroofing.com. Application details are for illustration purposes only and may not be appropriate for all environmental conditions, building designs or panel profiles. Projects should be designed to conform to applicable building codes, regulations and accepted industry practices.